

(19) World Intellectual Property Organization  
International Bureau



03 DEC 2004



(43) International Publication Date  
18 December 2003 (18.12.2003)

PCT

(10) International Publication Number  
WO 03/104355 A1

- (51) International Patent Classification<sup>7</sup>: C10G 2/00
- (21) International Application Number: PCT/EP03/05962
- (22) International Filing Date: 5 June 2003 (05.06.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
02253912.6 5 June 2002 (05.06.2002) EP
- (71) Applicant (for all designated States except US): SHELL  
INTERNATIONALE RESEARCH MAATSCHAPPIJ  
B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR  
The Hague (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): FENOUIL, Lau-  
rent, Alain [FR/GB]; 2 York Road, Waterloo, London SE1  
7NA (GB). GEIJSEL, Joannes, Ignatius [NL/NL]; Carel  
van Bylandtlaan 30, NL-2596 HR The Hague (NL). MO-  
HAMAD ALI, Abdul, Razak [MY/NL]; Carel van By-  
landtlaan 30, NL-2596 HR The Hague (NL).
- (74) Agent: SHELL INTERNATIONAL B.V.; Intellectual  
Property Services, P.O. Box 384, NL-2501 CJ The Hague  
(NL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,  
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,  
UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report  
— before the expiration of the time limit for amending the  
claims and to be republished in the event of receipt of  
amendments
- For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.



WO 03/104355 A1

(54) Title: PROCESS FOR THE PRODUCTION OF HYDROCARBONS FROM GASEOUS HYDROCARBONACEOUS FEED

(57) Abstract: Process for the production of hydrocarbons from gaseous hydrocarbonaceous feed comprising the steps of: i) partial oxidation conversion of the gaseous hydrocarbonaceous feed and oxygen containing gas at elevated temperature and pressure into synthesis gas; ii) catalytical conversion of synthesis gas of step i) using a cobalt based Fischer-Tropsch catalyst into hydrocarbons comprising stream; iii) separating the hydrocarbons comprising stream of step ii) into a hydrocarbons product stream and a recycle stream; and iv) removing carbon dioxide from the recycle stream and recycle of carbon dioxide depleted recycle stream to step i).

PROCESS FOR THE PRODUCTION OF HYDROCARBONS FROM  
GASEOUS HYDROCARBONACEOUS FEED

The present invention relates to a process for the production of hydrocarbons from gaseous hydrocarbonaceous feed.

5 This process comprises in general the conversion of a hydrocarbonaceous feed by partial oxidation using an oxygen containing gas into synthesis gas. Subsequently, this synthesis gas is catalytically converted into hydrocarbons using a Fischer-Tropsch catalyst.

10 US-A-4,046,829 discloses a method for producing hydrocarbons from coal using an iron based Fischer-Tropsch catalyst. Coal is gasified and synthesis gas formed is gas scrubbed and subsequently subjected to partial oxidation with oxygen. After the Fischer-Tropsch conversion of synthesis gas low hydrocarbons are  
15 separated, recycled and after carbon dioxide removal mixed with synthesis gas prior to the partial oxidation.

US-A-4,433,065 discloses a process for producing hydrocarbons from coal using a cobalt based Fischer-Tropsch catalyst. After removal of liquid hydrocarbons  
20 the gas phase is subject to carbon dioxide removal. After separation a hydrogen comprising stream is recycled to the partial oxidation process, a light hydrocarbons comprising stream is recycled to the coal gasification process, and a carbon monoxide comprising stream is  
25 subjected to combustion for electricity generation.

US-A-5,324,335 discloses a process for producing hydrocarbons using an iron-based Fischer-Tropsch catalyst in which hydrocarbon containing gas is subjected to steam

reforming for producing synthesis gas. After carbon dioxide removal the synthesis gas is subjected to the Fischer-Tropsch conversion. Light hydrocarbons are separated, recycled and mixed with the synthesis gas.

5       The present invention has for its object to provide a process for the production of relatively high hydrocarbons using a cobalt Fischer-Tropsch catalyst. More particularly, the invention concerns a cobalt catalyst, especially a cobalt-zirconia catalyst, which is  
10       favorable for producing a relative large amount of hydrocarbons in the C<sub>10</sub>-C<sub>14</sub> range beside a lighter and a heavier fraction. This favor for C<sub>10</sub>-C<sub>14</sub> hydrocarbons, especially unsaturated hydrocarbons, results however in a higher production of offgas when compared with a process  
15       which is optimal for the production of the most heavy paraffinic products. In modern concept plant design this offgas may not be flared but is to be used or reprocessed.

20       The present invention provides a solution to this problem with the process for the production of hydrocarbons from gaseous hydrocarbonaceous feed comprising the steps of:

- 25       i)       partial oxidation conversion of the gaseous hydrocarbonaceous feed and oxygen containing gas at elevated temperature and pressure into synthesis gas;
- ii)       catalytical conversion of synthesis gas of step i) using a cobalt based Fischer-Tropsch catalyst into a hydrocarbons comprising stream;
- 30       iii)      separating the hydrocarbons comprising stream of step ii) into a hydrocarbons product stream and a recycle stream; and

iv) removing carbon dioxide from the recycle stream and recycle of carbon dioxide depleted recycle stream to step i).

According to the process of the invention the hydrocarbons comprising stream is separated in a hydrocarbons product stream and a recycle stream. Carbon dioxide is removed from the recycle stream and the carbon dioxide depleted recycle stream is used as a feed for the partial oxidation conversion. Preferably at least 70 vol.% of carbon dioxide is removed, more preferably at least 80 vol.%, even more preferably at least 90 vol.%. The recycle stream comprises predominantly hydrogen, carbon monoxide, C<sub>1</sub> to C<sub>3</sub> hydrocarbon, in some cases also C<sub>4</sub> and minor amounts of C<sub>5</sub>+ hydrocarbon and inerts as nitrogen noble gasses.

A reprocessing of the recycle stream without prior carbon dioxide removal would have resulted in synthesis gas having a low H<sub>2</sub>/CO ratio which is inappropriate for use in the Fischer-Tropsch conversion of synthesis gas for the objected hydrocarbons. Direct use of the recycle stream in the partial oxidation conversion would provide synthesis gas with a too high level of inerts. Removal of carbon dioxide prior to use in the partial oxidation conversion will reduce the level of inerts in the synthesis gas produced. Use of the carbon dioxide depleted recycle stream in turn results in the use of less oxygen in the partial oxidation conversion. The recycle stream optimizes the carbon efficiency of the process. This in its turn increases the thermal efficiency of the process. Finally, removal of carbon dioxide requires less costs than a conversion of carbon dioxide in carbon monoxide.

According to the invention the process of the invention allows the use of a cobalt based Fischer-Tropsch catalyst, especially a cobalt on zirconia catalyst, which is favorable for the production of C<sub>10</sub>-C<sub>14</sub>, hydrocarbons whereas the offgas produced does not result in a extensive increase of costs and the amount of carbon dioxide to be removed is minimal due to the use of gaseous hydrocarbonaceous feed which results in a less production of carbon dioxide.

The process of recycling the carbon dioxide depleted recycle stream is simplified if this carbon dioxide depleted recycle stream is first compressed, mixed with gaseous hydrocarbonaceous feed and subsequently introduced in the partial oxidation conversion using oxygen containing gas.

In order to avoid a build-up of inerts in the process, it is preferred when part of the recycle stream of step iii), e.g. between 5 and 50 vol.%, preferably between 10 and 40 vol.%, of the total stream, is used as fuel in steam reforming of gaseous hydrocarbonaceous feed for producing hydrogen supplement for synthesis gas of step i).

Accordingly, inerts such as carbon dioxide and nitrogen are removed from the process after combustion as flue gas and the hydrogen or hydrogen rich synthesis gas produced in the SMR process may be used for adjusting the H<sub>2</sub>/CO ratio of the synthesis gas.

According to a further preferred embodiment part of the recycle stream of step iii) or step iv) is used as fuel for power generation.

Finally, it is preferred that the hydrocarbons product stream is subjected to catalytic hydrocracking.

Accordingly, the molecular weight distribution of hydrocarbons produced may be adjusted as desired.

The hydrocarbonaceous feed suitably is methane, natural gas, associated gas or a mixture of C<sub>1-4</sub> hydrocarbons. The feed comprises mainly, i.e. more than 90 v/v%, especially more than 94%, C<sub>1-4</sub> hydrocarbons, especially comprises at least 60 v/v percent methane, preferably at least 75 percent, more preferably 90 percent. Very suitably natural gas or associated gas is used. Suitably, any sulphur in the feedstock is removed.

The (normally liquid or solid) hydrocarbons produced in the process and mentioned in the present description are suitably C<sub>3-100</sub> hydrocarbons, more suitably C<sub>4-60</sub> hydrocarbons, especially C<sub>5-40</sub> hydrocarbons, more especially C<sub>6-20</sub> hydrocarbons, or mixtures thereof. These hydrocarbons or mixtures thereof are liquid or solid at temperatures between 5 and 30 °C (1 bar), especially at 20 °C (1 bar), and usually are paraffinic of nature, while up to 30 wt%, preferably up to 15 wt%, of either olefins or oxygenated compounds may be present.

The partial oxidation of gaseous feedstocks, producing mixtures of especially carbon monoxide and hydrogen, can take place in the oxidation unit according to various established processes. Catalytic as well as non-catalytic processes may be used. These processes include the Shell Gasification Process. A comprehensive survey of this process can be found in the Oil and Gas Journal, September 6, 1971, pp 86-90. The partial oxidation process may be carried out in combination with a reforming process, e.g. in the form of an autothermal reforming process.

The oxygen containing gas is air (containing about 21 percent of oxygen), or oxygen enriched air, suitably

containing up to 100 percent of oxygen, preferably containing at least 60 volume percent oxygen, more preferably at least 80 volume percent, more preferably at least 98 volume percent of oxygen. Oxygen enriched air  
5 may be produced via cryogenic techniques, but is preferably produced by a membrane based process, e.g. the process as described in WO 93/06041.

To adjust the  $H_2/CO$  ratio in the syngas, carbon dioxide and/or steam may be introduced into the partial  
10 oxidation process. Preferably up to 15% volume based on the amount of syngas, preferably up to 8% volume, more preferably up to 4% volume, of either carbon dioxide or steam is added to the feed. As a suitable steam source, water produced in the hydrocarbon synthesis may be used.  
15 As a suitable carbon dioxide source, carbon dioxide from the effluent gasses of the expanding/combustion step may be used. The  $H_2/CO$  ratio of the syngas is suitably between 1.5 and 2.3, preferably between 1.8 and 2.1. If desired, (small) additional amounts of hydrogen may be  
20 made by steam methane reforming, preferably in combination with the water shift reaction. Any carbon monoxide and carbon dioxide produced together with the hydrogen may be used in the hydrocarbon synthesis reaction or recycled to increase the carbon efficiency.

25 The percentage of hydrocarbonaceous feed which is converted in the first step of the process of the invention is suitably 50-99% by weight and preferably 80-98% by weight, more preferably 85-96% by weight.

The gaseous mixture, comprises predominantly  
30 hydrogen, carbon monoxide and optionally nitrogen, is contacted with a suitable catalyst in the catalytic conversion stage, in which the normally liquid hydro-carbons are formed. Suitably at least 70 v/v% of

the syngas is contacted with the catalyst, preferably at least 80%, more preferably at least 90, still more preferably all the syngas.

5 The catalysts used for the catalytic conversion of the mixture comprising hydrogen and carbon monoxide into hydrocarbons are known in the art and are usually referred to as Fischer-Tropsch catalysts. The catalysts for use in the Fischer-Tropsch hydrocarbon synthesis process comprises, as the catalytically active component  
10 cobalt.

The catalytically active cobalt is preferably supported on a porous carrier. The porous carrier may be selected from any of the suitable refractory metal oxides or silicates or combinations thereof known in the art.  
15 Particular examples of preferred porous carriers include silica, alumina, titania, zirconia, ceria, gallia and mixtures thereof, especially silica and titania.

The amount of catalytically active cobalt on the carrier is preferably in the range of from 3 to 300 pbw  
20 per 100 pbw of carrier material, more preferably from 10 to 80 pbw, especially from 20 to 60 pbw.

If desired, the cobalt based Fischer-Tropsch catalyst may also comprise one or more metals or metal oxides as promoters. Suitable metal oxide promoters may be selected  
25 from Groups IIA, IIIB, IVB, VB and VIB of the Periodic Table of Elements, or the actinides and lanthanides. In particular, oxides of magnesium, calcium, strontium, barium, scandium, yttrium, lanthanum, cerium, titanium, zirconium, hafnium, thorium, uranium, vanadium, chromium  
30 and manganese are most suitable promoters. Particularly preferred metal oxide promoters for the catalyst used to prepare the waxes for use in the present invention are manganese and zirconium oxide. Suitable metal promoters



may be selected from Groups VIIB or VIII of the Periodic Table. Rhenium and Group VIII noble metals are particularly suitable, with platinum and palladium being especially preferred. The amount of promoter present in the catalyst is suitably in the range of from 0.01 to 100 pbw, preferably 0.1 to 40, more preferably 1 to 20 pbw, per 100 pbw of carrier.

The catalytically active cobalt and the promoter, if present, may be deposited on the carrier material by any suitable treatment, such as impregnation, kneading and extrusion. After deposition of the cobalt and, if appropriate, the promoter on the carrier material, the loaded carrier is typically subjected to calcination at a temperature of generally from 350 to 750 °C, preferably a temperature in the range of from 450 to 550 °C. The effect of the calcination treatment is to remove crystal water, to decompose volatile decomposition products and to convert organic and inorganic compounds to their respective oxides. After calcination, the resulting catalyst may be activated by contacting the catalyst with hydrogen or a hydrogen-containing gas, typically at temperatures of about 200 to 350 °C.

The catalytic conversion process may be performed in the conversion unit under conventional synthesis conditions known in the art. Typically, the catalytic conversion may be effected at a temperature in the range of 150 to 350 °C, preferably from 180 to 270 °C. Typical total pressures for the catalytic conversion process are in the range of from 1 to 200 bar absolute, more preferably from 10 to 70 bar absolute. In the catalytic conversion process preferably (at least 50 wt% of C<sub>5</sub>+, preferably 70 wt%) C<sub>5</sub>-20 hydrocarbons are formed.

The amount of C<sub>10</sub>-C<sub>14</sub> which is directly formed in step ii) of the process is suitably between 12 and 27 wt% of the C<sub>5</sub>+ product stream, preferably between 17 and 27 wt%, more preferably between 22 and 27 wt%. A high amount is preferred as the C<sub>10</sub>-C<sub>14</sub> fraction is a valued LDF feedstock.

The average ASF value for the C<sub>5</sub>+ product stream of the step ii) of the process according to the present invention is suitable between 0.95 and 0.80, preferably between 0.92 and 0.82, preferably between 0.90 and 0.85. Higher values will result in a relative low amount of C<sub>10</sub>-C<sub>14</sub> fraction, lower values will result in too much C<sub>1</sub>-C<sub>4</sub> products, which products have a low value. The ASF value can be optimized by changing reaction conditions, especially H<sub>2</sub>/CO ratio and temperature, but also GHSV and pressure, and by a suitable choice of the catalyst. Especially a cobalt on zirconia carrier is suitable. The relative low ASF value (when compared with Fischer Tropsch processes directed to wax production) result in a relative large gas fraction to be recycled. CO<sub>2</sub> removal is especially suitable under those conditions.

The process according to the present invention is especially suitable for Fischer Tropsch plants which use a two or three stage Fischer Tropsch process. The relative low ASF values not only directly result in a large amount of C<sub>1</sub>-C<sub>4</sub> products, but these large amounts of gas also result (keeping any other variables the same) in an indirect increase of the C<sub>1</sub>-C<sub>4</sub> fraction in the second and third stage (H<sub>2</sub>/CO ratio and GHSV).

The cobalt-based Fischer-Tropsch catalyst used, yields substantial quantities of paraffins, more preferably substantially unbranched paraffins. A part may

boil above the boiling point range of the so-called middle distillates. The term "middle distillates", as used herein, is a reference to hydrocarbon mixtures of which the boiling point range corresponds substantially to that of kerosene and gas oil fractions obtained in a conventional atmospheric distillation of crude mineral oil. The boiling point range of middle distillates generally lies within the range of about 150 to about 360 °C.

The higher boiling range paraffinic hydrocarbons, if present, may be isolated and subjected in an optional hydrocracking unit to a catalytic hydrocracking which is known per se in the art, to yield the desired middle distillates. The catalytic hydro-cracking is carried out by contacting the paraffinic hydrocarbons at elevated temperature and pressure and in the presence of hydrogen with a catalyst containing one or more metals having hydrogenation activity, and supported on a carrier. Suitable hydrocracking catalysts include catalysts comprising metals selected from Groups VIB and VIII of the Periodic Table of Elements. Preferably, the hydrocracking catalysts contain one or more noble metals from group VIII. Preferred noble metals are platinum, palladium, rhodium, ruthenium, iridium and osmium. Most preferred catalysts for use in the hydro-cracking stage are those comprising platinum.

The amount of catalytically active metal present in the hydrocracking catalyst may vary within wide limits and is typically in the range of from about 0.05 to about 5 parts by weight per 100 parts by weight of the carrier material.

Suitable conditions for the optional catalytic hydrocracking in a hydrocracking unit are known in the

art. Typically, the hydrocracking is effected at a temperature in the range of from about 175 to 400 °C. Typical hydrogen partial pressures applied in the hydrocracking process are in the range of from 10 to 250 bar.

The process may conveniently and advantageously be operated in a recycle mode or in a single pass mode ("once through") devoid of any recycle streams. This single pass mode allowing the process to be comparatively simple and relatively low cost.

The recycle stream obtained after separation of the hydrocarbons may comprise normally gaseous hydrocarbons produced in the synthesis process, nitrogen, unconverted methane and other feedstock hydrocarbons, unconverted carbon monoxide, carbon dioxide, hydrogen and water. The normally gaseous hydrocarbons are suitably C<sub>1-5</sub> hydrocarbons, preferably C<sub>1-4</sub> hydrocarbons, more preferably C<sub>1-3</sub> hydrocarbons. These hydrocarbons, or mixtures thereof, are gaseous at temperatures of 5-30 °C (1 bar), especially at 20 °C (1 bar). Further, oxygenated compounds, e.g. methanol, dimethylether, may be present. For the removal of carbon dioxide any suitable conventional process may be used, for instance adsorption processes using amines, especially in combination with a physical solvent, such as the ADIP process or the SULFINOL process as described in inter alia GB 1,444,936; GB 1,131,989; GB 965,358; GB 957260; and GB 972,140. Suitably at least 70 vol.% of the carbon dioxide present is removed from the recycle stream, preferably 80 vol.%, more preferably 90 vol.%. Suitably, between 50 and 90 vol.% of the recycle stream is recycled to step i) of the process, preferably between 60 and 80 vol.%, in order to

get an optimum balance between optimum carbon use,  
process efficiency and inert removal.

C L A I M S

1. Process for the production of hydrocarbons from gaseous hydrocarbonaceous feed comprising the steps of:
  - i) partial oxidation conversion of the gaseous hydrocarbonaceous feed and oxygen containing gas at elevated temperature and pressure into synthesis gas;
  - ii) catalytical conversion of synthesis gas of step i) using a cobalt based Fischer-Tropsch catalyst into a hydrocarbons comprising stream;
  - iii) separating the hydrocarbons comprising stream of step ii) into a hydrocarbons product stream and a recycle stream; and
  - iv) removing carbon dioxide from the recycle stream and recycle of carbon dioxide depleted recycle stream to step i).
2. Process as claimed in claim 1, wherein the carbon dioxide depleted recycle stream is premixed with the gaseous hydrocarbonaceous feed.
3. Process as claimed in claim 1 or 2, wherein part of the recycle stream of step iii) is used as fuel in steam reforming of gaseous hydrocarbonaceous feed for producing hydrogen supplement for synthesis gas of step i).
4. Process as claimed in claims 1-3, wherein part of the recycle stream of step iii) or step iv) is used as fuel for power generation.
5. Process as claimed in claim 1-4, wherein the hydrocarbons product stream is subjected to catalytic hydrocracking.
6. Process as claimed in claim 1-5, wherein the catalyst is a cobalt-zirconia catalyst.

7. Process as claimed in claim 1-6, wherein the hydrocarbon product stream comprises between 17 and 27 wt% C<sub>10</sub>-C<sub>14</sub>, preferably between 22 and 27 wt%.

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 03/05962

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C10G2/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2 243 869 A (KEITH JR PERCIVAL C ET AL) 3 June 1941 (1941-06-03) claim 2 page 3, right-hand column, line 60 - page 4, left-hand column, line 31 figure 1 page 2, right-hand column, line 18 - line 22	1,2
A	WO 01 96264 A (CONOCO INC) 20 December 2001 (2001-12-20) claims 9,10	1,6
A	NL 8 303 911 A (SHELL INT RESEARCH) 3 June 1985 (1985-06-03) claims 1-3,8,11,14	1,5

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Z" document member of the same patent family

Date of the actual completion of the international search

7 November 2003

Date of mailing of the international search report

13/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl  
Fax (+31-70) 340-3016

Authorized officer

De Herdt, O



# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/05962

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2243869	A	03-06-1941	NONE	
WO 0196264	A	20-12-2001	AU 6838101 A	24-12-2001
			WO 0196264 A1	20-12-2001
			US 2003022949 A1	30-01-2003
			US 2002183404 A1	05-12-2002
NL 8303911	A	03-06-1985	CA 1234396 A1	22-03-1988

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**